

ONYX

Built to perform, built to last.



Order Picking Truck 1.0T

OP2-4

FEATURES

- **Designed to match operator preferences**, offering a familiar and efficient user experience similar to high-lifting order pickers.
- **Versatile mid-level order picker**, suitable for a range of warehouse applications.
- **Ideal for e-commerce fulfilment centres** and medium-to-high-level distribution facilities.

Model			OP2-4 (3600)
Drive			Electric
Load capacity	Qy	kg	1000/136
Wheelbase	h6	mm	1365
Service weight	h3	kg	1965
Height of overhead guard	h4	mm	2270
Lift height	l2	mm	3600
Height, mast extended	b1/b2	mm	5975
Overall length	h12	mm	2750
Overall width	Wa	mm	860
Stand height, elevated	h12	mm	3815
Turning radius	Wa	mm	1600
Travel speed, laden/unladen		km/h	8/8
Lifting speed, laden/unladen		m/s	0.13/0.16
Lowering speed, laden/unladen		m/s	0.16/0.18
Max. gradeability, laden/unladen		%	0
Drive motor rating S2 60 min		kW	4
Battery voltage/nominal capacity		V/Ah	24/360



Order Picking Truck 1.0T

OP2-4

Options

Key: • Standard • Optional

No.	Optional Items	OP2-4 (4800)
1.1	Fork dimension	• 1000*600 2A 100*40*1070 • 1000*600 2A 100*40*1200
2.1	Load wheel type	• Single
2.2	Load wheel material	• Rubber
2.3	Drive wheel material	• PU
2.7	Battery capacity	• 360AH
2.8	Charger	• 24V-50A External
2.9	Battery indicator	• With time
2.12	Safe hook	• No
2.13	Traction pin	• No
2.14	Electrostatic chain	• No
2.15	Entry roller	• No
3.3	Castor wheels	• Yes and not customised
3.4	Water auto-filling system	• No
3.7	Warning lamp	• Rear warning lamp
3.9	Blue lamp	• No
3.12	Buzzer	• Descending buzzer
3.18	Guide wheel	• No
3.19	USB interface	• No
4.1	Battery side pull function	• Yes and not customised
4.7	Overhead guard	• Yes and not customised
5.1	Battery side pull attachment	• No